

Contact us: Consulting: +49 (0)36259 300 99

Support: +49 (0)36259 300 711

E-Mail: contact@haecker-automation.com



DISPENSER D-PT CARTRIDGE TEMPERATURE CONTROL

SKU: \$2-0020.03 **16.900,00** € excl. VAT



Categories: Dispensing systems, Modules

BESCHREIBUNG

The D-PT dispenser is a pressure-time controlled dispenser that dispenses various materials directly from the cartridge.

The cartridge is pressurized for a defined time, thereby dispensing the appropriate amount of material. A retaining vacuum within the cartridge prevents further leakage of the dispensed material, thus guaranteeing a precise dispensing result.

The dispenser also includes a cartridge temperature control (Peltier element) to keep the dosing material in the cartridge at a constant temperature during processing, in order to create uniform processing conditions. Cartridge temperature control allows for temperature adjustment of \pm 10 K relative to the machine's internal temperature.

A monitoring camera mounted on the dosing head ensures constant monitoring of the process.

Häcker Automation GmH Inselsbergstraße 17 99880 Waltershausen / OT Schwarzhausen



Contact us:

Consulting: +49 (0)36259 300 99 Support: +49 (0)36259 300 711

E-Mail: contact@haecker-automation.com

MORE INFORMATIONS

Dimensions in mm (W x D x H) $49 \times 310 \times 518$

Weight in kg 5,6

Movement range in Z in mm 150

Cartridge holder SEMCO 30 cc

Voltage in V 24

Max. current in A 4

Communication interface UNICAN

Operating temperature in °C 20 ... 35





