

Contact us: Consulting: +49 (0)36259 300 99

Support: +49 (0)36259 300 711

E-Mail: contact@haecker-automation.com



DISPENSER D-PT PERFECDOS VALVE (FOR OURPLANT XTEC)

SKU: \$2-0020.04/05 **27.900,00** € excl. VAT



Categories: Dispensing systems, Modules

BESCHREIBUNG

The dispenser D-PT is a pressure-time-controlled dispenser that dispenses various materials with an additional perfecdos valve. The dispenser was specially designed for the OurPlant XTec.

The material is dispensed quickly and precisely thanks to the integrated valve. The cartridge, which is attached to the valve, is permanently pressurized with a defined pressure. By opening the valve for a defined time and displacing the material due to the applied compressed air and tappet movement in the valve, a corresponding amount of material is dispensed. The dispensing amount of liquid is depending on the opening time of the valve, fluid pressure, nozzle and tappet type and viscosity of the liquid.

An observation camera which is installed on the dispensing head, thereby ensuring the constant control of the process.

A pressure reservoir with a 400ccm tank is additional connected between compressed air machine supply and the perfecdos valve.

MORE INFORMATIONS

Dimensions in mm (W x D x H) $49 \times 310 \times 520$

Dimensions pressure reservoir in mm (W x D x H) $60 \times 182 \times 322.5$

Weight in kg 6.0

Häcker Automation GmH Inselsbergstraße 17 99880 Waltershausen / OT

Schwarzhausen



Contact us: Consulting: +49 (0)36259 300 99

Support: +49 (0)36259 300 711

E-Mail: contact@haecker-automation.com

Gewicht Druckspeicher in kg 3.1

Movement range in Z in mm 150

Cartridge holder SEMCO 10 cc, 30 cc

Volume pressure reservoir in I 0.4

Voltage in V 24

Max. current in A 4

Communication interface UNICAN

Operating temperature in °C 20 ... 35









